

NEW



Available in Sheet and Tile

- Cost effective homogeneous general purpose floorcovering
- Factory finish surface treatment provides base for maintenance
- Good resistance to everyday wear
- Extremely low VOCs contributing to better interior air quality
- Minimum 25% recycled content – helping the environment

HOMOGENEOUS VINYL
FLOORCOVERING

**Vylon
Plus**



581 Light warm grey
[weld rod 1292319] LRV 53.70



594 Ivory
[weld rod 1287334] LRV 64.02



595 Champagne
[weld rod 1287098] LRV 52.20



596 Straw
[weld rod 1287426] LRV 39.73



597 Canary
[weld rod 1287099] LRV 42.00



582 Medium warm grey
[weld rod 1287291] LRV 40.42



587 Sand medium
[weld rod 1287597] LRV 39.57



585 Hessian
[weld rod 1287174] LRV 40.78



588 Sand dark
[weld rod 1287380] LRV 22.78



589 Brown beige
[weld rod 1287498] LRV 24.31



593 Bermuda
[weld rod 1287105] LRV 15.20



584 Marina
[weld rod 1288312] LRV 29.91



580 Light blue
[weld rod 1287523] LRV 55.38



586 Artic
[weld rod 1287446] LRV 57.13



592 Frost
[weld rod 1287027] LRV 45.26



590 Dolphin
[weld rod 1287086] LRV 28.60



591 Charcoal
[weld rod 1292459] LRV 15.11



583 Grey white
[weld rod 1287338] LRV 65.17

HOMOGENEOUS VINYL
FLOORCOVERING

Vylon Plus

Specification

Vylon Plus is a homogeneous vinyl floorcovering with a factory finish surface protection for easier initial maintenance. Ideal for use in commercial and domestic locations. Product standard EN649

Make your balanced choice

Tarkett's approach to sustainability is all about giving our customers simple and clear information so they can make the right choice of flooring, balancing their project and budget requirements against the need of sustainable solutions. That's why all of our products come with a special tag giving the essential information about sustainability and environmental health.



Choose to use good materials



Select flooring produced with fewer resources



Ensure safer, healthier products in people-friendly spaces




Participate in reuse and recycling of products

Tarkett's commitments to VOC* emissions

Volatile organic compounds (VOCs) are emitted as gases from manmade materials such as flooring as well as natural ones like trees. To improve indoor air quality, Tarkett has invested significantly in the research of raw materials and flooring manufacturing processes to reach near zero emission levels. Since September 2011 all Tarkett's homogeneous vinyl flooring has emissions below quantifiable level - measuring less than 10 µg/m³ TVOC after 28 days*. All other floorings that Tarkett manufactures currently release less than 100 µg/m³ TVOC after 28 days - ten times lower than European standards. We'll continue to focus on safer, healthier solutions to reduce emission levels across all products, for improved indoor air quality and a healthier quality of life.

* ISO standards 16000-3/-6/-9/-11






Classification	Standards	Vylon Plus
Type of floorcovering	EN649	Homogeneous vinyl floorcovering
Classification	EN685	Commercial 34 Industrial 43
Technical Characteristics	Standards	Vylon Plus
Total thickness	EN 428	2.0mm
Total weight	EN 430	3700g/m ²
Form of delivery	EN 426 EN 427	Rolls: 20lm x 2m 21000 ___ (3 digit colour no.) Tile: 610mm x 610mm 21007 ___ (3 digit colour no.) 16 tiles/box = 5.95m ² per box Tile: 300mm x 300mm 21001 ___ (3 digit colour no.) 50 tiles /box= 4.5m ²
Technical Performances	Standards	Vylon Plus
Surface treatment		Factory finish
Abrasion group	EN 660: Part 2	Group M: ≤7.50mm ³
Residual indentation	EN 433	Approx. 0.04mm
Castor chair test	EN 425	Suitable
Dimensional stability	EN 434	≤0.40 % for rolls ≤0.25 % for tiles
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Bfl s1 ≥8 kW/m ² Pass
Marine equipment	IMO FTPS Part 5 & 2 IMO Res A653	 0575
Slip resistance	DIN 51130 EN 13893	R9 ≥0.3
Electrostatic properties	EN 1815	<2 kV
Light fastness	EN ISO 105-B02	≥6
Chemical resistance	EN 423	Good resistance
Thermal resistance	EN 12524	0.01 m ² K/W
Underfloor heating		Suitable - Max 27°C
Colours		18

The above information is subject to modifications for the benefit of further improvement. (01/2013)
For more detailed technical information please contact Tarkett. Follow Tarkett's installation and maintenance instruction carefully, available on request



Homogeneous to EN 649 have a generic A+ environmental rating in major use areas such as healthcare, education and retail.
www.bre.co.uk/greenguide



Vylon Plus 01/2013

Tarkett Limited Lenham, Maidstone, Kent ME17 2QX, United Kingdom. Tel 01622 854040 Fax 01622 854520 www.tarkett.co.uk Email: uksales@tarkett.com



www.tarkett.co.uk